LED MAGNETIC TRACK Light



Working voltage

Operating Current

Frequency Power factor

Lumen flux

Efficacy

Color Temperature (CCT)

Working Temperature

Working humidity

Lighting Distance Body Material

Brand of driver

Brand of chip





SAFA® Lighting System		MORANO
Model	3043	
Rated Power	30W	
Body size	Ø68*H155mm	
Light weight	472g	

The average of initial power shall not exceed the rated power by more than

Model	3043	
Rated Power	30W	
Body size	Ø68*H155mm	
Light weight	472g	
Lamp Power	The initial power shall not exceed the rated by more than 10%	
	The average of initial power shall not exceed the rated power by	

7.5%

48V

0.75A 50/60Hz

>0.95

>2700Lm

>90Lm/watt

6500K/4000K/3000K

Surge protection-OVP (48V)

LUX distance from 10-12 meter

Flickers free Safety Earthling

Aluminum

LEIPUSEN

OSRAM

Form -40°C to 60°C Form 5% to 90%

Color rendering index (CRI)	≥90	
Driver efficiency	>90%	
Beam angel	24°	
Dimmable	Not Optional	
Life Time	≥43800hrs	
IP Grade	IP20	
	Over voltage protection-OVP (<48V)	
	Under voltage protection-UVP (>36V)	
	Over current protection-OCP (0.75A)	
Protection	Thermal protection-OHP (>75℃)	